



STEEL SPECIFICATIONS

	CARRIAGE HOUSE DESIGN								TRADITIONAL DESIGN							
	CLASSICA 1000	CLASSICA 2000	CLASSICA 3000	OAK SUMMIT 1000	OAK SUMMIT 2000	OAK SUMMIT 3000	FIMBEL DC-400	FIMBEL DC-500	HERITAGE 1000	HERITAGE 2000	HERITAGE 3000*	STRATFORD 1000	STRATFORD 2000	STRATFORD 3000**	FIMBEL OLYMPUS 400	FIMBEL OLYMPUS 500
PANEL DESIGNS	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓		
Short									•	•	•	•	•	•	•	•
Long									•	•	•	•	•	•		
Flush									•	•	•	•	•	•		
Ribbed											•			•		
Carriage House	8 Designs	8 Designs	8 Designs	3 Designs	3 Designs	3 Designs	1 Design	1 Design								
CONSTRUCTION LAYERS																
Steel	•			•					•			•				
Steel + Insulation		•			•				•			•				
Steel + Insulation + Steel			•			•	•	•		•			•	•	•	•
DOOR THICKNESS																
1 3/8" (3.5cm)						•	•							•	•	
2" (5.1cm)	•	•	•	•	•			•	•	•	•	•	•			•
INSULATION		Polystyrene ¹	Polyurethane ¹		Polystyrene ¹	Polystyrene ¹	Polyurethane	Polyurethane		Polystyrene ¹	Polystyrene ¹		Polystyrene ¹	Polystyrene ¹	Polyurethane	Polyurethane
R-VALUE²		6.84	13.35		6.84	6.58	11.04	15.67		6.84	9.19		6.84	6.58	11.04	15.67
STEEL THICKNESS																
Gauge (ga)	24 ga	24 ga	25/27 ga	25 ga	25 ga	27/27 ga	27/27 ga	27/27 ga	24 ga	24 ga	24/27 ga	25 ga	25 ga	27/27 ga	27/27 ga	27/27 ga
Gauge (mm)	0.61mm	0.61mm	0.53/0.42	0.53mm	0.53mm	0.42/0.42mm	0.42/0.42	0.42/0.42	0.61mm	0.61mm	0.61/0.42	0.53mm	0.53mm	0.42/0.42	0.42/0.42	0.42/0.42
WOODGRAIN EXTERIOR TEXTURE	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
END STILES																
Galvanized	•	•		•	•							•	•			
Painted			•			•	•	•	•	•	•			•	•	•
THERMAL SEAL						•	•	•		•				•	•	•
BOTTOM WEATHER SEAL	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Steel Retainer	•	•	•	•	•				•	•		•	•			
Aluminum Retainer						•					•			•		
Duo-Durometer Astragal							•	•							•	•
DECORATIVE WINDOW OPTIONS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WINDOW GLASS OPTIONS																
3/32" (0.24cm) Single Strength				•	•		•	•	•	•	•	•	•	•	•	•
1/8" (0.32cm) Tempered Double Strength	•	•	•													
Insulated Glass			•			•	•	•			•			•	•	•
Obscure (not shown)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
DECORATIVE HARDWARE OPTIONS	•	•	•	•	•	•	•	•								
EXTERIOR COLOR OPTIONS																
True White	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Almond				•	•	•		•	•	•	•	•	•	•	•	•
Sandtone	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•
Brown								•	•	•	•			•	•	•
Hunter Green														•		
Gray														•		
Dark Woodgrain	•	•	•			•								•		
WIND LOAD³ AVAILABLE	•	•	•	•	•	•			•	•	•	•	•	•		
WARRANTY																
Paint Finish ⁴	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime	Lifetime
Workmanship/Hardware ⁴	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	5 Years	Lifetime	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	5 Years	Lifetime

✓ Amarr's section interfaces are designed to reduce the risk of serious finger and hand injuries.

* Formerly WeatherGuard™ Plus
** Formerly WeatherGuard™

¹ All Insulation on Amarr brand doors has passed fire safety testing.

² Calculated door section R-value is in accordance with DASMA TDS-163.

³ It is your responsibility to make sure your garage door meets local building codes.

⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

NOTE: Optional door locks and various heights and widths are available thru your local garage door dealer.

Amarr, Amarr Classica Collection, Classica Collection, Classica, Stratford, and WeatherGuard are registered trademarks of Amarr Company, North Carolina, U.S.A.

Amarr Company's products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents.

165 Carriage Court
Winston-Salem, NC 27105
800.503.DOOR
www.amarr.com

©2010 Amarr Garage Doors
Printed in USA Form #6171009/1M/AGD

Amarr reserves the right to change specifications and designs without notice and without incurring obligations.

WOOD COMPOSITE SPECIFICATIONS

	JELD-WEN® ESTATE	JELD-WEN® CARRIAGE HOUSE	JELD-WEN® TRADITIONAL
PANEL DESIGNS			
Short			•
Long			•
Carriage House	8 Designs	7 Designs	
DECORATIVE WINDOW OPTIONS		•	•
CONSTRUCTION: Wood Composite + Insulation + Wood Composite	•	•	•
DOOR THICKNESS	1 5/8" (4.1cm)	1 5/8" (4.1cm)	1 3/8" (3.5cm)
POLYSTYRENE INSULATION	•	•	•
R-VALUE ²	7.98	7.98	7.08
BOTTOM WEATHERSEAL	•	•	•
WINDOW GLASS OPTION: 1/8" (0.3cm) Tempered Double Strength		•	•
DECORATIVE HARDWARE OPTIONS	•	•	
EXTERIOR COLOR OPTIONS			
White	•	•	•
Portabello	•	•	•
Primed	•	•	•
WIND LOAD ¹ AVAILABLE	•	•	•
SECTION WARRANTY ³	5 Years	5 Years	Lifetime
HARDWARE WARRANTY ³	3 Years	3 Years	3 Years



¹ It is your responsibility to make sure your garage door meets local building codes.

² Calculated door section R-value is in accordance with DASMA TDS-163.

³ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

NOTE: Doors available in various heights and widths. Contact your local garage door dealer for specific details.

JELD-WEN® primed composite doors require painting or staining on all six sides. Instructions for painting and staining are available at amarr.com.

JELD-WEN is a registered trademark of JELD-WEN, Inc., Oregon, U.S.A. Amarr distributes JELD-WEN® brand product under a national distribution agreement.

WOOD SPECIFICATIONS

	BOB TIMBERLAKE® COLLECTION	BILTMORE™ FOR YOUR HOME COLLECTION	AMARR BY DESIGN COLLECTION
PANEL DESIGNS			
Carriage House	5 Designs	6 Designs	Unlimited Designs
CONSTRUCTION*: Wood + Insulation + Wood	•	•	•
DOOR THICKNESS	3" (7.6cm)	3" (7.6cm)	3" (7.6cm)
WOOD BASEPLY OPTIONS			
5/8" MDO Plywood (paint grade only)		•	•
1/2" Marine Grade Plywood		•	•
5/8" Incense Cedar	•	•	•
5/8" Clear Vertical Grain Cedar	•	•	•
5/8" Spanish Cedar	•	•	•
5/8" Mahogany		•	•
Other materials available upon request		•	•
TRIM OVERLAY OPTIONS			
5/8" Moisture- and Rot-resistant Extria Exterior Panel (paint grade only)		•	•
5/8" Incense Cedar	•	•	•
5/8" Clear Vertical Grain Cedar	•	•	•
5/8" Spanish Cedar	•	•	•
5/8" Mahogany		•	•
Other materials available upon request		•	•
OPTIONAL WOOD DISTRESSING			•
SECTION HEIGHT OPTIONS	18", 21", 28", or 32"	18", 21", 28", or 32"	18", 21", 28", or 32"
POLYSTYRENE INSULATION (1 3/8" thick)	•	•	•
BOTTOM WEATHERSEAL	•	•	•
DECORATIVE WINDOW OPTIONS			
1/8" (0.32cm) Double Strength	•	•	•
Seeded	•	•	•
Straw		•	
OPTIONAL DECORATIVE HARDWARE	•	•	•
WIND LOAD ¹ AVAILABLE*	•	•	•
SECTION WARRANTY ²	1 Year	1 Year	1 Year



* Optional: Wood-on-steel section construction is available. Some wind load pressures may require wood-on-steel section construction.

¹ It is your responsibility to make sure your garage door meets local building codes.

² For complete warranty details, visit amarr.com or contact your local Amarr dealer.

Doors are shipped natural. Priming is available for paint grade doors. All doors require finishing on all six (6) sides of each section within two days of receipt of door(s) and prior to installation. Visit amarr.com for finishing recommendations.